



BUS Cable al/pet+Cu braid 1x2x0,22mm² LSZH

BUS



Construction	
Conductor	Flexible Tinned Cu Class 5
Insulation	PE
1° Shield	Al/PET + drain wire
2° Shield	Tinned Cu Braid
Sheath	LSZH Grey RAL 7001
Printing	ECS-CAVO PER SISTEMI DI COLLEGAMENTO BUS RS485 1x2x0,22 LSZH – CEI UNEL 36762 C-4 (U ₀ =400v) WW/YY [NR ORD]001MT – Eca

Electrical Properties	
Nominal Voltage	300/300V
Test Voltage	2000V
Operating temperature (fixed lay without stress)	-20°C +70°C
Minimum installation temperature	+5°C
Resistance a 20°C (Ω/km)	according to IEC 228/HD 383 S2

Rules
CEI UNEL 36762 C-4 (U ₀ =400V) – BT 93/68 CEE – 2014/35/EU – 2011/65/CE (RoHS II) – 2015/863/EU (RoHS 3) – 2006/1907/CE (Reach)

Applications
RS-485

Smart code	Item number	Section mm ²	Twisting step	Spirals /meter	Diameter mm.	Weight Kg/Km
BHS-222	BUHFRS0222SAGRB05	1x2x0,22	50mm	20	6.70	57.00

} The details expressed above have to be considered as an indication.

European Cable Service S.r.l. - Tel. +39 0583 436283 - www.europeancableservice.it - info@europeancableservice.it