



Cable ECS-7 TV 75Ω

Coaxial Cables



Construction	
Conductor	Solid Bare CU 1.13 +/- 0.012mm
Dielectric	FOAM PE 4.8 +/- 0.15mm
Shield	Al/PET/Al
Second shield	Tinned CU Braid >40%
Outer sheath	PVC white 6.7 +/- 0.20mm
Printing	ECS – ECS-7 75 OHM \varnothing 5.00 EN50117-2-4 CEI UNEL36762 C-4 (U _o =400V) CE 001m WW/YY Eca

Electrical properties	
Standard impedance	75.0 +/-3.0 Ω
Mutual capacitance	52.0 +/-2.0pF/m
SRL dB	5-1000 MHz \geq 221000-2000 MHz \geq 20
VPP	85%

Notes
UV resistant outer sheath

Frequency(MHz)	Attenuation @20°C (dB/100m)
100	4.90
200	6.70
300	8.50
500	11.90
800	16.30
1000	17.40

Smart code	Item number	Diameter mm.	Weight Kg/Km
ECS-7	SKPV75D67XCSBIM01	6.7 +/- 0.20	29.00

} The details expressed above have to be considered as an indication.

European Cable Service S.r.L. - Tel. +39 0583 436283 - www.europeancableservice.it - info@europeancableservice.it