

**FFROR**

# Cable FFROR Orange Extra-Flex

## Instrumentation and Control Cable



Construction	
Conductor	Flexible Bare Cu Class 6
Insulation	PVC (color according to UNEL 00722)
Outer Sheath	PVC Orange
Printing	ECS-CAVO UTENSILE FFROR 300/500V Nr. cond. x sez. [ORDER n. - YY/WW] 001m - Eca

Electrical Properties	
Nominal Voltage	300/500V
Test Voltage	2000V
Operating Temperature	-10°C +70°C
Minimum Bending radius	6 x ext.diam

Rules
CEI EN 60228 / CEI EN 50363 / CEI EN 60332-1-2

Smart Code	Internal Item	Section mm <sup>2</sup>	Diameter mm.	Weight Kg/Km
UT-210	UTPVRN0210FXARM01	2×1,00	5.60	51.50
UT-310	UTPVRN0310FGARM01	3G1,00	5.90	62.00
UT-215	UTPVRN0215FXARM01	2×1.50	6.80	74.00
UT-315	UTPVRN0315FGARM01	3G1.50	7.20	90.00
UT-415	UTPVRN0415FGARM01	4G1.50	8.10	116.00
UT-325	UTPVRN0325FGARM01	3G2.50	8.90	143.00
UT-425	UTPVRN0425FGARM01	4G2.50	9.70	176.00

} The details expressed above have to be considered as an indication.

