



## Cables FRO-HP-OB Cca s3,d1,a3

### Instrumentation and Control Cable



Construction	
Conductor	Flexible bare Cu class 5
Shield	PVC DIN47100
Sheath	PVC grey
Printing	FRO-HP 300/500V Nr. cond. x sez. [ORDER n. – YY/WW] 001m – Cca-s3,d1,a3

Electrical properties	
Nominal voltage	300/500V
Test voltage	2000V
Operating temperature	-15°C +70°C
Min bending radius	10 x ext.diam.

Rules
CEI 20-29 EN 50525-2-11 PQA / IEC 60228 CL.5 . EN 50575:2014 + EN 50575/A1:2016

Smart code	Item number	Section mm <sup>2</sup>	Diameter mm.	Weight Kg/Km
FH-025	FHPVRN0250FXGRM01	2×0,50	5.20	32.00
FH-045	FHPVRN0250FXGRM01	4×0,50	6.00	47.00
FH-065	FHPVRN0650FXGRM01	6×0.50	6.60	64.00
FH-085	FHPVRN0850FXGRM01	8×0.50	8.00	83.00
FH-105	FHPVRN1050FXGRM01	10×0.50	9.10	101.00
FH-125	FHPVRN1250FXGRM01	12×0.50	9.30	115.00
FH-145	FHPVRN1450FXGRM01	14×0.50	9.70	131.00
FH-165	FHPVRN1650FXGRM01	16×0.50	10.40	151.00

} The details expressed above have to be considered as an indication.

European Cable Service S.r.l. - Tel. +39 0583 436283 - [www.europeancableservice.it](http://www.europeancableservice.it) - [info@europeancableservice.it](mailto:info@europeancableservice.it)