



F.O.cable 9/125 OS2 Ind./Out.LSZH-Dielectric Armour Optical Fiber



Fiber details	
Type	G.657A1
Mode field diameter	1310nm: 9,0 ±0.4µm / 1550nm: 10,1 ±0.5µm
Cladding diameter	124,8 ±0.7µm
Cladding non-circularity	≤0,7%
Core-Cladding concentricity error	≤ 0,5µm
Coating diameter	245 ±5µm
Coating non-circularity	≤6,0%
Cladding-Coating concentricity error	≤ 12µm
Cable Cutoff Wavelength	$\lambda_{cc} \leq 1260\text{nm}$
Attenuation coefficient (max.)	1310nm ≤0,40 dB/km – 1550nm ≤0,30 dB/km
Macro-Bending Loss	1 turn x 10mm radius @1550nm: ≤0,75dB 1 turn x 10mm radius @1625nm: ≤1,50dB


Construction Characteristics	
Tubes	1
Diameter of tube	2,10mm ±0.1mm
Loose tube material	PBT
Loose tube color	Natural
Colored Coating Fiber	dimension: 250µm±15µm color: blue, orange, green, brown, grey, white, red, black
Strength member	Glass Yarn
Sheath wall thickness	1,3mm ±0.1mm
Diameter	5,50mm ±0.2mm

Environmental and mechanical Performances	
Long term tension	300N
Short term tension	600N
Long term crush	300N/10cm
Short term crush	1000N/10cm
Min. bending radius (static lay)	10 x Diam. ex.
Min. bending radius (dynamic lay)	20 x Diam. ex.
Operating temperature/storage	-30°C ~ +60°C
Laying temperature/installation	-20°C ~ +50°C

Outer sheath	
Type	LSZH Yellow
Printing	ECS – Number FO OS2 9/125 G657 OUTDOOR-INDOOR LSZH Eca ORDER NR. METER MARKING

Tests	Rules	Value	Approval parameters
Traction	IEC 60794-1-21-E1	600N	$\Delta\alpha \leq 0,25$ dB/km – Fiber draw ratio $\leq 0,45\%$
Crush	IEC 60794-1-21-E3	1000N/100mm (maximum 15 minutes)	$\Delta\alpha \leq 0,05$ dB – No damage
Crash	IEC 60794-1-21-E4	2.5 Nm, 3 impacts, R= 300mm	$\Delta\alpha \leq 0,05$ dB
Torque	IEC 60794-1-21-E7	100N, $\pm 180^\circ$ 10 cycles	$\Delta\alpha \leq 0,05$ dB – No damage
Repeated bending	IEC 60794-1-21-E11	20xD., 1Kg, 3 cycles	$\Delta\alpha \leq 0,05$ dB – No damage
Bending radius	IEC 60794-1-21-E6	R=20xD., 4 turns, 3 cycles	$\Delta\alpha \leq 0,05$ dB – No damage
Temperature cycling	IEC 60794-1-22-F1	-20°C ~ +70°C	Maximum value 0,05 dB/km

Smart code	Item Number	Nr Fiber	Diameter mm.	Weight Kg/Km	Min. bending radius
FOS2-08	FOHFFD08EIS2GIB40	8	5,5mm	38.00	10xExt.Diam.



} The details expressed above have to be considered as an indication.

European Cable Service S.r.L. - Tel. +39 0583 436283 - www.europeancableservice.it - info@europeancableservice.it