



MINICOAX HD BLUE LSZH

Coaxial Cables



Construction	
Conductor	Bare Cu 0.41 mm
Dielectric	FOAMED PE 1.95 ±0.10mm
First shield	Al/PET/Al
Second shield	Tinned Cu braid62%
Sheath	LSZH blue RAL5015 Diam.3.50 ±0.10mm
Printing	ECS-MINICOAX 75OHM HD LSZH CEI UNEL 36762 C-4 Uo=(400V) WW/YY 001m – Eca

Electrical properties	
Conductor resistance	<320.0 Ω/km at 20°C
Standard impedance	<75.0 ±3Ω
Capacitance	<56.0 ±3.0pF/m
SRL dB	30-470 MHz >28470-862 MHz >23
Screen effect dB	100-900 MHz >85
Min bending radius	min. 20mm
Signal trasmission	CVBS: 400m HD-SDI: 70m

Frequency(MHz)	Attenuation @20°C (dB/100m)
5	3.70
10	4.70
50	11.00
100	15.30
200	21.00
300	26.10
470	33.10
600	37.90

800	43.80
862	46.00
1000	49.90

Smart code	Item number	Diameter mm.	Weight Kg/Km
SN-35H	SMHF75D35HSABLM01	3.50 ±0.10	15.60

} The details expressed above have to be considered as an indication.

European Cable Service S.r.L. - Tel. +39 0583 436283 - www.europeancableservice.it - info@europeancableservice.it