



SAT 75Ω 6,5mm

Coaxial Cables



Construction	
Conductor	Cu clad steel 1,02 ±0.01mm
Dielectric	FOAM PE 4.60 ±0.15mm
First shield	Al/PET/Al
Second shield	Al braid
Sheath	PVC white 6.50 ±0.20mm
Printing	ECS-SAT 75 OHM Diam.6.5 EN 50117-2-4 CEI UNEL 36762 C-4 (Uo=400V) CE 001m WW/YY – Eca

Electrical properties	
Standard impedance	<75.0 ±3Ω
Capacitance	<52.0 ±2.0pF/m
SRL dB	5-1000 MHz >221000-2000 MHz >20
VPP	85%

Frequency(MHz)	Attenuation @20°C (dB/100m)
55	5.60
187	9.30
211	10.00
400	13.50
500	15.00
750	18.50
860	20.00
1000	21.50

Smart code	Item number	Diameter mm.	Weight Kg/Km
------------	-------------	--------------	--------------

ST-650	STPV75D65XTABIM01	6.50 ±0.20	35.00
---------------	--------------------------	-------------------	--------------

} The details expressed above have to be considered as an indication.

European Cable Service S.r.l. - Tel. +39 0583 436283 - www.europeancableservice.it - info@europeancableservice.it