



# Videointercom Cable LSZH

## Security Alarm cable



Construction	
Conductor	Flexible Bare Cu class 5
Insulation	LSZH
Outer Sheath	LSZH Green RAL 6018
Printing	ECS-CAVO VIDEOCITOFONICO LSZH 1X2X1.00 CEI UNEL 36762-C-4 (U <sub>0</sub> =400v) WW/YY Eca

Electrical properties	
Nominal Voltage	300/500V
Test Voltage	4000V
Operating Temperature	-10°C +70°C
Min. Bending radius	10 x diam. est.

Rules
CEI 20-29 IEC 60228 CEI 20-11 CEI 20-35 IEC 60332-1-2 CEI 20-22 II IEC 60332-3 CEI UNEL 36762 CEI 20-20/12/1-2-3

Notes:
Twisting step 60mm (n.16 spires/m); suitable for indoor and outdoor lay (in channels).

Smart Code	Item nr.	Section mm <sup>2</sup>	Diameter mm.	Weight Kg/Km
VH-210 /M100	VCHFRN0210FXVEM01	1x2x1,00	5.60	40.00
VH-210 /B500	VCHFRN0210FXVEB05	1x2x1,00	5.60	40.00

} The details expressed above have to be considered as an indication.

European Cable Service S.r.L. - Tel. +39 0583 436283 - [www.europeancableservice.it](http://www.europeancableservice.it) - [info@europeancableservice.it](mailto:info@europeancableservice.it)